

# 2CX30 SPEAKER CABLE RED/PURPLE(50M)



## **Technical info**

| Type: 2Cx30              |               | Length: 50M         |
|--------------------------|---------------|---------------------|
| Conductor                | The number    | 2x30                |
|                          | Diameter (mm) | 0.13 <u>±</u> 0.005 |
| Insulation               | AVG (mm)      | ≥0.8                |
|                          | Mix (mm)      | ≥0.64               |
| Outer diameter (mm)      |               | 2.6x5.2             |
| Standard: JB/T 8734-2012 |               |                     |

### Stock code

| No.           | Description                        |
|---------------|------------------------------------|
| CAS2318.GL-AM | CCM 2CX30 SPEAKER CABLE RED/PURPLE |

Note: Due to continuous development and improvement, our company reserves the right to change specification without notice.



# 2CX26/0.254 P/P SPEAKER CABLE(300MR)



#### **Technical info**

| Type: 2Cx26              |               | Length: 300MR      |
|--------------------------|---------------|--------------------|
| Carakiratan              | The number    | 2x26               |
| Conductor                | Diameter (mm) | 0.2 <u>+</u> 0.005 |
| Insulation               | AVG (mm)      | ≥0.6               |
|                          | Mix (mm)      | ≥0.48              |
| Sheath                   | AVG (mm)      | ≥0.6               |
|                          | Mix (mm)      | ≥0.48              |
| Outer diameter (mm)      |               | 6                  |
| standard: GB/T 5023-2008 |               |                    |

### Stock code

| No.          | Description                       |
|--------------|-----------------------------------|
| CAS226P3.WF- | CCM 2CX26/0.254 P/P SPEAKER CABLE |

Note: Due to continuous development and improvement, our company reserves the right to change specification without notice.