



Main

Range	ARGUS
Product or component type	Occupancy sensor
Load type	Halogen lamp <= 1000 VA Energy saving lamp <= 80 VA Incandescent lamp <= 2000 W Low voltage halogen lamp <= 1000 VA Fluorescent lamp 100 µF <= 900 VA

Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	360°
Presence detection area	PIR: 360°, 7 x 7 m
Device mounting	Flush Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	111 mm
Depth	66 mm

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 flush mounting IP44 surface mounting
Ambient air temperature for operation	0...45 °C indoor -20...45 °C outdoor
Standards	EN 60669-1 EN 60669-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	281.82 g
Package 1 Height	7.5 cm
Package 1 width	12 cm
Package 1 Length	12 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Distributed By:

Choo Chiang Marketing Pte Ltd
(a subsidiary of Choo Chiang Holdings Ltd)
did: +65 6368 5922 | fax: +65 6363 5922
Head Office: 10 Woodlands Loop S(738388)
website: www.choochiang.com | facebook: facebook.com/choochiang.sg

