



SENTRYSOCKET®

RANGE INTRODUCTION

Sentrysocket provides a high level of protection against electrocution and is available in 4 MK wiring device ranges to suit most applications.

FEATURES & BENEFITS

ACTIVE CONTROL CIRCUIT

This version of Sentrysocket incorporates a 'RE-SET' mechanism and is mains failure sensitive i.e. it will function under all normal conditions expected of an RCD but it will also trip in the event of a power cut or a dramatic reduction in mains voltage. This makes it ideal for use where hazardous situations could occur due to equipment such as rotating machinery and heat developing apparatus becoming suddenly energised after a power cut.

PASSIVE CONTROL CIRCUIT

This version of Sentrysocket incorporates a 'STAY-SET' mechanism and is mains failure proof i.e. it will function under all normal conditions expected of an RCD but will not trip in the event of a power cut. This makes it suitable for freezers or use in inaccessible or unmanned locations.

All Sentrysockets are pulsating D.C. and A.C. fault current sensitive products



RCD PROTECTED SWITCHCKET OUTLETS

13 AMP LOGIC PLUS FLUSH



K6400WHI



K6403WHI



K6231WHI



K6233WHI

K6400WHI

1 GANG DP, 30mA RATED, TRIPPING CURRENT, ACTIVE CONTROL CIRCUIT

K6403WHI

1 GANG DP, 30mA RATED, TRIPPING CURRENT, PASSIVE CONTROL CIRCUIT

K6231WHI

2 GANG SP, 30mA RATED, TRIPPING CURRENT, ACTIVE CONTROL CIRCUIT

K6233WHI

2 GANG SP, 30mA RATED, TRIPPING CURRENT, PASSIVE CONTROL CIRCUIT

MOUNTING BOXES

Flush: 886ZIC - 35mm deep
Boxes must have a minimum depth of 30mm

SURFACE

K2140WHI, 30mm deep, products have up to 15mm thick frontplates

DIMENSIONS

86 x 146mm

FIXING CENTRES

120.6mm

BS7288:2016

EN61543:1995+A12:2005,A2:2006

ALBANY PLUS FLUSH



K6401BSS



K6404BSS



K6402ALM



K6405ALM

K6401BSS

1 GANG DP
30mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

K6404BRC

1 GANG DP
30mA RATED TRIPPING CURRENT
PASSIVE CONTROL CIRCUIT

MOUNTING BOXES

Flush: 886ZIC - 35mm deep
Boxes must have a minimum depth of 30mm

SURFACE

with knockouts: K897ALM
without knockouts: K830ALM

DIMENSIONS

86 x 146mm

FIXING CENTRES

120.6mm

BS7288:2016

EN61543:1995+A12:2005,A2:2006

METALCLAD PLUS SURFACE



K6402ALM



K6405ALM



K6231ALM



K6233ALM

K6402ALM

1 GANG DP
30mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

K6405ALM

1 GANG DP
30mA RATED TRIPPING CURRENT
PASSIVE CONTROL CIRCUIT

DIMENSIONS

86 x 147 x 54mm

KNOCKOUTS

8 x 20mm

Three in top side, two in bottom side, one in each end and one in base

SPARE BOX

K897ALM

BS7288:2016

EN61543:1995+A12:2005,A2:2006



K6231ALM

2 GANG SP
30mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

K6233ALM

2 GANG SP
30mA RATED TRIPPING CURRENT
PASSIVE CONTROL CIRCUIT

DIMENSIONS

86 x 147 x 54mm

KNOCKOUTS

8 x 20mm

Three in top side, two in bottom side, one in each end and one in base

SPARE BOX

K897ALM

BS7288:2016

EN61543:1995+A12:2005,A2:2006

MASTERSEAL PLUS IP66 SURFACE



K56201GRY



K56231GRY



K56231WHI

K56201GRY

1 GANG DP
30mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

K56231GRY

2 GANG SP
30mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

K56233GRY

2 GANG SP
30mA RATED TRIPPING CURRENT
PASSIVE CONTROL CIRCUIT

Fixing holes are for No.8 woodscrews (not supplied).

Supplied with an earth terminal in the back box. The Sentrysocket has 5 entries. Suitable for supply voltage of 240V a.c.

Standard Shutters

DIMENSIONS

157 x 175 x 89mm

BS7288:2016

EN61543:1995+A12:2005,A2:2006

IP66 BS EN 60529:1992

ALL SENTRY SOCKETS ARE PULSATING D.C. AND A.C. FAULT CURRENT SENSITIVE PRODUCTS:
It is important to ensure that the correct control circuit, active or passive, is selected for each application.
Suitable for supply voltage of 240V a.c.

Distributed By:

Choo Chiang Marketing Pte Ltd

(a subsidiary of Choo Chiang Holdings Ltd)

did: +65 6368 5922 | fax: +65 6363 5922

Head Office: 10 Woodlands Loop S(738388)

website: www.choochiang.com | facebook: [facebook.com/choochiang.sg](https://www.facebook.com/choochiang.sg)

Honeywell International Middle East

Customer Service Tel +971 4 450 5800

Customer Service Fax +971 4 450 5900

E-mail mkenquiries.me@Honeywell.com

www.mkelectric.com

???????

© 2019 Honeywell International Inc.



CHOO CHIANG

SINGAPORE
QUALITY CLASS



bizSAFE

ISO9001
CERTIFIED



LASTING
CONNECTIONS

100
YEARS