

Exit Light

Designed to be slim and lightweight, low power consumption, low EMI and specially equipped with a customised proprietary Hybrid IC and super bright white LED and longer life-span. Easy and fast installation.

Suitable for Factories, Schools, Sports Stadiums, Banks, Club Houses, Hotels, Computer Rooms, Offices, Public Halls, Hospitals, Apartments, Warehouses, Carparks, etc



TECHNICAL CHARACTERISTICS

Description:	Emergency exit EXIT
Material	Housing: Electro galvanized steel with epoxy powder coating
Finishes	Diffuser: Acrylic
Colour:	Colour: White
3-Hrs Battery Pack:	Comply
Colour Temperature:	6500K
Colour rendering index:	80
Lamp type:	LED
Dimension:	L=327mm; W=40mm; H=239mm
Mounting:	Surface or recess
Average life span:	50,000 hours (LED & Driver)
IP rating:	20
Wattage, W:	1W (LED)
Control gear:	Integral

IP20

HYBRID IC CONTROLLED
SELF-CONTAINED EMERGENCY LED
TWIN LIGHT

SUPER BRIGHT 1W SMT NICHIA WHITE
LED LAMP

LOW POWER CONSUMPTION

Stock code

No.	Description
EXLSLEDE.EDL	EDGE LINE BY CCM EL.SEW.NC180.M SINGLE SIDE SURFACE LED EXIT LIGHT(PSB) <E
EXLSLEDT.EDL	EDGE LINE BY CCM EL.SEE.NC180.M SINGLE SIDE SURFACE LED EXIT LIGHT(PSB) >T
EXLSLED.EDL	EDGE LINE BY CCM EL.SE.NC180.M SINGLE SIDE SURFACE LED EXIT LIGHT(PSB)
EXLSLEDDS.EDL	EDGE LINE BY CCM EL.DEE.NC180.M DOUBLE SIDE SURFACE LED EXIT LIGHT(PSB) ONE SIDE <E ONE SIDE >T
EXLRP.EDL	RECESS PLATE FOR EDGE LINE BY CCM LED EXIT LIGHT

Note: Due to continuous development and improvement, our company reserves the right to change specification without notice.

VISIT CCM ONLINE ccm.sg

DIMENSION (mm)

