



PNE 300A CONVERSION KITS FOR MOST LED LIGHTS FIXTURES



Model & Dimension :



PNE 300A
185L x 30W x 25H



CS4NC
101L x 25W x 50H



BS4NC
205L x 25W x 25H

SPECIFICATION

Model	: PNE 300A/ T4/ T10/ C
System Mode	: Maintained / Non Maintained
Emergency Duration	: 2 hours (3 hours available)
Lamp	: SMD L.E.D. STRIP
Battery	: 4.8V High temperature nickel cadmium battery
Recharge Period	: 16 – 24 hours
Battery Protection	: Low Voltage cut off to prevent from over discharging
Monitoring	: Green L.E.D. "ON" indicates charging Equipped with push test switch to simulate power failure
Input Voltage	: 240V 50Hz
Charger	: Constant current
Housing	: Injection molding fire retardant ABS housing
Dimension	: 185L x 30W x 25H
Weight	: 0.85kg
Mounting	: Fitting Mounted
Warranty	: 1 Year
Compliance	: SS 563 : 2010, IEC 6147-2-7
Power Consumption	: 3.20 Watt

Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.

Distributed By:

Choo Chiang Marketing Pte Ltd
(a subsidiary of Choo Chiang Holdings Ltd)
did: +65 6368 5922 | fax: +65 6363 5922
Head Office: 10 Woodlands Loop S(738388)
website: www.choochiang.com | facebook: facebook.com/choochiang.sg

PNE translite PTE LTD

CO REG NO.: 199100450H

