

TEL 32 SELF-CONTAINED EMERGENCY LUMINAIRES (LED)



Dimension: 300L x 130W x 64H

SPECIFICATION

Model

System Mode

Emergency Duration

Lamp

Battery

bullery

Recharge Period

Battery Protection

Monitoring

Input Voltage

Charger

Housing

Dimension

Waight

Weight

Mounting

Warranty
Compliance

Power Consumption

IP Rating

: TEL 32

: Non Maintained

: 2 hours

: 2 x 1W High Output white L.E.D.

: 3.6V High temperature nickel cadmium battery

: 16 - 24 hours

: Low Voltage cut off to prevent from over discharging

: Green L.E.D. "ON" indicates charging

Equipped with push test switch to simulate power failure

: 240V 50Hz +/10%

: Constant current, Dual rate

: Injection moulded fire retardant ABS housing

: 300L x 130W x 64H

: 0.9kg

: Surface mounted direct to wall

: 1 Year

: SS 563: 2010, SS IEC 60598-2-22

: 3.90 Watt

: IP 20

Note: Due to continuous development and improvement, our company reserves the right to change specifications without notice.

PNE TRANSLITE PTE LTD

CO REG NO.: 199100450H

Distributed By

Choo Chiang Marketing Pte Ltd (a subsidiary of Choo Chiang Holdings Ltd) did: +65 6368 5922 | fax: +65 6363 5922 Head Office: 10 Woodlands Loop S(738388)











